

1	2	3	4	5	6			
			REV	DESCRIPTION	DATE	ECO	APPR	
<p>Note.</p> <p>1. Specification</p> <p>1.1 Frequency : 690MHz ~ 2800MHz</p> <p>1.2 PIM : -165dBc max with 2 x 20W tones @ room temp</p> <p>1.3 Impedance : 50 Ohm nom</p> <p>1.4 Return Loss : 20dB min</p> <p>2. Material and Finish</p> <p>2.1 Body : Tri-Alloy Plated Brass</p> <p>2.2 Socket : Silver plated Beryllium copper</p> <p>2.3 INSULATOR : PTFE</p> <p>3. 2002/95/EC(RoHS) compliant</p>								
<p>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE ;</p> <p>1 PLACE DECIMAL 2 PLACE DECIMAL ANGLES 1.6a</p> <p>± 0.20 mm ± 0.10 mm ± 1°</p> <p>REMOVE BURRS. BREAK SHARP EDGES</p>			<p>MATERIAL</p> <p>See Note 2</p>	<p>DRAWN</p> <p>2013.12.06</p>	<p>TITLE</p> <p>ADAPTOR PIMD N Female to N Female Straight Type</p>			
			<p>FINISH</p> <p>See Note 2</p>	<p>ENGINEER</p>	<p>SCALE</p> <p>N / A</p>		<p>SHEET</p> <p>1 of 1</p>	
			<p>REFERENCE</p>	<p>APPROVED</p>	<p>DATE</p>	<p>DRAWING No.</p> <p>DWPIM-AD-NFNF</p>		
			<p>CAD FILE</p> <p>CAD:/PIMD_TEST/</p>	<p>DWG SIZE</p> <p>A4</p>	<p>REV.</p> <p>A</p>			